# **Environmental Protection Agency**

later than 180 days after its initial startup, you must meet the two limitations specified in paragraphs (a)(1) and (2) of this section.

- (1) The opacity limitation is 10 percent (6-minute average), except as described in paragraph (a)(2) of this section.
- (2) The opacity limitation is 35 percent (6-minute average) during the startup period that is within the first 30 minutes of operation.
- (b) The limitations in paragraph (a) of this section apply at all times except during malfunctions.

#### § 60.2972 How must I monitor opacity for air curtain incinerators that burn only wood waste, clean lumber, and yard waste?

- (a) Use Method 9 of appendix A of this part to determine compliance with the opacity limitation.
- (b) Conduct an initial test for opacity as specified in §60.8.
- (c) After the initial test for opacity, conduct annual tests no more than 12 months following the date of your previous test.
- (d) If the air curtain incinerator has been out of operation for more than 12 months following the date of the previous test, then you must conduct a test for opacity upon startup of the unit.

#### § 60.2973 What are the recordkeeping and reporting requirements for air curtain incinerators that burn only wood waste, clean lumber, and yard waste?

- (a) Prior to commencing construction on your air curtain incinerator, submit the three items described in paragraphs (a)(1) through (3) of this section.
- (1) Notification of your intent to construct the air curtain incinerator.
  - (2) Your planned initial startup date.
- (3) Types of materials you plan to burn in your air curtain incinerator.
- (b) Keep records of results of all initial and annual opacity tests in either paper copy or computer-readable format that can be printed upon request, unless the Administrator approves another format, for at least 5 years. You must keep each record on site for at least 2 years. You may keep the

records off site for the remaining 3 years.

- (c) Make all records available for submittal to the Administrator or for an inspector's review.
- (d) You must submit the results (each 6-minute average) of the initial opacity tests no later than 60 days following the initial test. Submit annual opacity test results within 12 months following the previous report.
- (e) Submit initial and annual opacity test reports as electronic or paper copy on or before the applicable submittal date.
- (f) Keep a copy of the initial and annual reports on site for a period of 5 years. You must keep each report on site for at least 2 years. You may keep the reports off site for the remaining 3 years.

#### § 60.2974 Am I required to apply for and obtain a title V operating permit for my air curtain incinerator that burns only wood waste, clean lumber, and yard waste?

Yes, if your air curtain incinerator is subject to this subpart, you are required to apply for and obtain a title V operating permit as specified in §§ 60.2966 and 60.2967.

## EQUATIONS

### § 60.2975 What equations must I use?

(a) Percent oxygen. Adjust all pollutant concentrations to 7 percent oxygen using equation 1 of this section.

$$C_{adj} = C_{meas} * (209-7) (209-80_2)$$
 (Eq.1)

Where:

 $C_{\rm adj} = {\rm pollutant}$  concentration adjusted to 7 percent oxygen

 $C_{\mathrm{meas}}$  = pollutant concentration measured on a dry basis

(20.9–7) = 20.9 percent oxygen–7 percent oxygen (defined oxygen correction basis)

20.9 = oxygen concentration in air, percent  $\%O_2$  = oxygen concentration measured on a dry basis, percent

(b) Capacity of a very small municipal waste combustion unit. For very small municipal waste combustion units that can operate continuously for 24-hour periods, calculate the unit capacity based on 24 hours of operation at the maximum charge rate. To determine the maximum charge rate, use one of two methods: